

VALVE ACTUATION LINKAGE MECHANISM

FIELD OF THE INVENTION

[0001] This invention relates generally to valve trains in internal combustion engines. More particularly, this invention relates to valve actuation mechanisms using rocker arms and valve bridges to actuate intake and exhaust valves in a diesel engine.

BACKGROUND OF THE INVENTION

[0002] Internal combustion engines typically have rocker arms to actuate intake and exhaust valves, which permit air to enter and exit each cylinder. Commonly there are separate rocker arms to actuate a valve or pair of valves. Push rods cause the rocker arms to rotate or pivot and thereby actuate the valves. The push rods extend through the engine to connect to a camshaft. As the camshaft rotates, the push rods move the rocker arms to open and close the valves. The camshaft is designed to open and close the valves in conjunction with the cycling of the piston in the cylinder.

[0003] Recent valve actuation mechanism designs use rocker carriers and rocker arm assemblies with rocker arms made of plate material. For example, those disclosed in patent applications S/N 09/768,520 filed on January 24, 2001, by Martin Zielke for a Rocker Carrier, and S/N 09/769,610 filed on January 25, 2001 by Danesh et al. for a Rocker Arm Assembly, which are hereby incorporated by reference. These patent applications are both assigned to the assignee of the present patent application, International Truck and Engine Corporation. The recent designs though improved over earlier designs have some drawbacks.

[0004] Figure 1 illustrates a perspective view of a partial prior art valve actuation mechanism. There is shown a valve actuation linkage mechanism 100 generally comprising a valve bridge 10, a pivot foot 20, a pivot foot fastener 30 and a rocker arm 40.

[0005] Figure 2 shows how the partial valve actuation mechanism of Figure 1, without the valve bridge, mounted on a rocker carrier 200 which will be mounted on a cylinder head (not shown) in an internal combustion engine. The rocker arms 40 and 240 are cooperatively mounted on the rocker carrier 200 through a corresponding rocker arm pedestal or fulcrum plate 220 and fastened to the rocker carrier 200 by hold down bolts 210. The hold down bolts 210 allow the rocker arms 40 and rocker arm fulcrum plate 220 to be pre-installed to the rocker carrier 200 thereby decreasing engine manufacturing time and costs. The rocker carrier 200 shown would be mounted on one side or bank of a V-8 type engine. The rockers arms 40 and 240 shown in Figure 2 typically have the same configuration but differ in size. Figure 2 shows the exhaust rocker arm 40 longer and larger than the intake rocker arm 240. However, length and size of the rocker arms 40 and 240 is determined by the location of the intake and exhaust valves in relation to the rocker arm assembly. The rocker arms could be the same or different sizes depending on a particular engine application.

[0006] Referring again to Figure 1, the valve actuation linkage mechanism 100 could be used in an engine application having four valves per cylinder. The valve bridge 10 when actuated by the rocker arm 40 via the pivot foot 25 will act on a pair of valves, e.g., a pair of intake or exhaust valves (not shown). The rocker arm generally comprises a push rod cup 60, a pivot ball cup 70, a rocker arm aperture 80, and a pivot foot end 55 having a pivot foot cup 50. The pivot foot cup 50 accepts a pivot foot 20 secured by a pivot foot fastener 30. The pivot foot fastener 30 secures the pivot foot 20 to the pivot foot cup 50 via a set of opposing pivot foot clamps 37 which are clamp or crimped on to the exterior surface of the pivot foot cup 50.

[0007] During engine operation, a push rod (not shown) actuates the rocker arm 40 via the push rod cup 60. The rocker arm 40 will pivot via a gage or pivot ball (not shown) in the pivot

ball cup 70. The pivot foot 20 will in turn actuate the valves (not shown) via the Valve Bridge 10. The pivot foot 20 contacts and acts on the valve bridge 10 to actuate valve movement (not shown) in a particular cylinder. In particular, the pivot foot bottom 25 contacts the valve bridge 10 at a top bridge contact surface area 15 to actuate valve movement. The physical makeup and positioning of the valve actuation linkage mechanism 100 is such that the of the pivot foot bottom 25 is continuously sitting on or contacting the valve bridge 10 top contact surface area 15. In this manner, rocker arm 40 movement and force is immediately translated, via the pivot foot 20, to the valve bridge 10.

[0008] As the rocker arm 40 moves and pivots during engine operation, the attached pivot foot pivot travels or cycles upward or downward in an arc motion. The pivot foot's 25 arcing motion and simultaneous mechanical contact on the valve bridge 10 results in friction wear between the pivot foot 20 and the bridge contact area 15. In essence, the pivot foot bottom surface 25 travels on the bridge contact area 15 and exerts a force with both vertical 13 and horizontal 17 elements. As the rocker arm 40 pivots during engine operation, the pivot foot bottom surface 25 exerts both a vertical force 13 and a back and forth horizontal force 17. The mechanical action between the pivot foot 20 and the valve bridge 10 results in excessive friction wear between the pivot foot contact surface 27 and the bridge contact area 15. Additionally, the pivot foot fastener 30 encounters vertical 13 and horizontal 17 forces. This degrades and loosens the connection securing the pivot foot 20 to the rocker arm 40 pivot foot cup 50. Moreover, the physical orientation and configuration of the rocker arm 40, pivot foot 20, pivot foot fastener 30 and valve bridge 10 prevent adequate oil lubrication of these interconnected and interactive parts, adding to the friction wear drawback of this design.

[0009] Thus, existing valve actuation linkage mechanisms suffer from excessive wear between the pivot foot and valve bridge at the point of contact or contact area. Accordingly, there is a need for a valve actuation linkage mechanism that can be pre-assembled and that reduces friction wear on the valve assembly during operation.

SUMMARY OF THE INVENTION

[0010] The present invention provides a valve actuation linkage mechanism for use in an internal combustion engine that reduces friction wear on the valve assembly during engine operation and can be pre-assembled resulting in decreased manufacturing time and cost. The valve actuation linkage mechanism comprises a rocker arm having a pivot rod cup, a pivot rod, a valve bridge having a pivot rod chamber, and a pivot rod retainer. The pivot rod comprises a pivot rod head, a pivot rod neck, a pivot rod body, and a pivot rod bottom. The valve bridge comprises a middle valve bridge section having the pivot rod chamber and at least one adjacent pivot rod retainer securing bore, a bottom valve bridge section, and a lubricant dimple in the pivot rod chamber. The pivot rod retainer is comprised of a pivot rod orifice having at least one pivot rod prong and at least one securing orifice.

[0011] The following drawings and description set forth additional advantages and benefits of the invention. More advantages and benefits are obvious from the description and may be learned by practice of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The present invention may be better understood when read in connection with the accompanying drawings, of which:

[0013] Figure 1 shows a perspective view of a prior art valve actuation assembly;

[0014] Figure 2 shows a perspective view of the prior art valve actuation linkage mechanism of Figure 1 installed on a rocker carrier;

[0015] Figure 3 shows a perspective view of an embodiment of a valve actuation linkage mechanism according to the present invention;

[0016] Figure 4 shows a side view of the embodiment of a valve actuation linkage mechanism shown in Figure 3;

[0017] Figure 5 shows a perspective view of another embodiment of the valve actuation linkage mechanism according to the present invention;

[0018] Figure 6 shows a perspective view of a pivot rod and valve bridge of the valve actuation linkage mechanism of Figure 3; and

[0019] Figure 7 shows a side view of the pivot rod and valve bridge of the valve actuation linkage mechanism of Figure 6.

DESCRIPTION OF THE INVENTION

[0020] Figure 3 illustrates a perspective view of a preferred embodiment of a valve actuation linkage mechanism 300 according to the present invention. The valve actuation linkage mechanism 300 comprises a valve bridge 310, a pivot rod 320, a pivot rod retainer 330 and a rocker arm 40. The valve actuation linkage mechanism 300 depicted in Figure 3 is preferably used in a 4-valve per cylinder engine application. Those of skill in the art will readily recognize that other engine applications are possible.

SAB [0021] The rocker arm 40 of the valve actuation linkage mechanism 300 shown in Figure 3 retains substantially the same function and physical configuration as existing prior art rocker arms 40 (shown in Figure 1). The rocker arm 40 will cooperate with the pivot rod 320 in the valve actuation linkage mechanism 300 to actuate the valve bridge 310. The novel pivot foot

preferably comprises a pivot rod head 329, a pivot rod neck 327, and a pivot rod body 325 with a pivot rod bottom 425 (shown in Figure 4). The pivot rod head 329 preferably has a curved shape in the form of a "mushroom" head. In this manner, the pivot rod head 329 will complementarily cooperate with a pivot rod cup 350 in the rocker arm 40. The complementary shapes of the curved pivot rod head 329 and the pivot rod cup 350 allow for easier motion between the two part and tend to reduce wear between them as the valve actuation linkage mechanism 300 operates.

[0022] Figure 3 also illustrates a novel valve bridge 310 that will act simultaneous on a pair of intake or exhaust valves (not shown). The valve bridge in this embodiment, the valve bridge 310 preferably comprises a pivot rod chamber 315, a pair of fastener bores 314, valve stem chambers 405 (shown in Figure 4), a bottom valve bridge section 312 and a middle valve bridge section 316. The pivot rod chamber 315 is preferably configured to be a hollow cylindrical void or chamber with a complementary pivot rod body 325 configuration that allows insertion of the pivot rod 320. Significantly, the configuration of the pivot rod bottom 425 and corresponding pivot rod chamber bottom 415 (shown in Figure 4) in the valve bridge 310 will eliminate the flat surface rubbing contact 15 present in prior designs thereby substantially reducing friction wear between linkage mechanism 300 components, particularly between the pivot foot bottom 25 and the valve bridge contact surface area 15 (shown in Figure 1). Additionally, the pivot rod chamber 315 is preferably configured such that there is a divot or dimple 417 (shown in Figure 4) at the pivot chamber bottom 415. The pivot or dimple 417 will preferably hold engine oil or some other lubricant to provide lubrication between the pivot rod 320 and the valve bridge 310. In particular, lubrication between the pivot rod bottom 425 and the pivot chamber bottom 415

(shown in Figure 4), thereby substantially reducing friction wear between the pivot rod 320 and the valve bridge 310.

[0023] The pivot rod chamber 315 is preferably located in the middle valve bridge section 316 and can be cast as part of or drilled into the valve bridge 310. The middle valve bridge section 316 can be either a raised body portion as shown here in Figure 3 or flush as illustrated in Figure 1 depending on the engine application. The bottom valve bridge section 312 is preferably a raised body portion that extends away and downward from the valve bridge 310. The bottom valve bridge section 312 is preferable since it will provide the valve bridge 310 with added structural support and strength, as there is now a pivot rod chamber 315 in the valve bridge 310. The actual configuration of the bottom valve bridge section 312 will be determined by the particular engine application used. Also, the fastener bores 314 are typically bored into the valve bridge 310 adjacent to the pivot rod chamber 315. The fastener bores 314 allow the pivot rod 310 to be secured in the pivot rod chamber 315 via the pivot rod retainer 330 (shown in Figures 6 & 7).

[0024] The pivot rod retainer 330 is preferably flat and comprises a pivot rod retaining area 335, a pair of pivot rod retaining prongs 337, and a pair of opposing fastener orifices 334. The pivot rod retainer 330 will have a thickness, length and width that will be dependent on the particular engine application where it 330 is to be used. The pivot rod retaining prongs 337 are preferably situated in opposing positions in the pivot rod retaining area 335 adjacent to the fastener orifices 334. The pivot rod 320 can be preferably inserted into the pivot rod retainer 320 either before or after the pivot rod retainer is secured to the valve bridge 310. The pivot rod retaining area 335 is configured in a manner so that the pivot rod 320, once inserted, can move as necessary as the rocker arm 40 goes through its motion during engine operation. The novel pivot

rod retainer 330 and the valve bridge 310 have moved the previous prior retaining or securing location of the pivot foot 20 from the rocker arm 40 pivot foot cup 50 to the valve bridge 310.

[0025] In a first case, the pivot rod 320 is inserted into the pivot rod retainer 330 before the retainer 330 is fastened to the valve bridge 310. The pivot rod body 325 is inserted into and travels in the pivot rod retaining area 335. The retaining prongs 337 are resilient and flex or move to allow the pivot rod body 325 to travel in pivot rod retaining area 335. Once the pivot rod body 325 has traveled sufficiently, the retaining prongs 337 will resiliently rebound or flex to secure the pivot rod retainer 330 to the pivot rod 320 around the pivot rod neck 327. The connected pivot rod 320 and pivot rod retainer 330 tandem would now be fastened to the valve bridge 310 (shown in Figures 6 & 7). The pivot rod 320 is inserted into the pivot rod chamber 315 of the valve bridge 310. The retainer 330/pivot rod 320 combination is then preferably secured to the valve bridge by using a pair of valve bridge fasters 614 (shown in Figures 6 & 7), e.g., drill screws or rivets.

[0026] In a second case, the pivot rod retainer 330 is first secured to the valve bridge 310 by a pair of fasters 614 inserted into the valve bridge fastener bores 314 (shown in Figures 6 & 7). The pivot rod 320 is next inserted into the pivot rod retainer 330 so that the pivot rod body 325 travels in the pivot rod retaining area 335. The resilient retaining prongs 337 flex or move to allow the pivot rod body 325 to travel in the pivot rod retaining area 335. Once the pivot rod body 325 has traveled sufficiently, the retaining prongs 337 will resiliently rebound or flex to secure the pivot rod 320, about the pivot rod neck 327, to the valve bridge 310 in the pivot rod chamber 315 (shown in Figures 6 & 7).

[0027] Once the pivot rod 320 has been secured to the valve bridge 310, the rocker arm 40 can interact or cooperate with the pivot rod 320/valve bridge 310 combination in the valve

actuation linkage mechanism 300 to actuate corresponding valves (not shown). During operation of the valve actuation linkage mechanism 300, the pivot rod 320 will operate in a manner substantially similar to that of a push rod (not shown). The pivot rod 320 rotates freely and moves about the pivot rod head 329 and pivot rod bottom 425 (shown in Figure 4) as necessary to account for the rotation and translation required for a 4-valve per cylinder engine requiring a valve bridge 310. There is enough play or space in the pivot rod retaining area 335 so that the pivot rod body 325 can move back and forth or vertically to translate the motion of the rocker arm 40 to the valve bridge 310 to appropriately actuate the valves (not shown) during engine operation.

[0028] Figure 4 illustrates a side view of the valve actuation linkage mechanism 300 shown in Figure 3. There is shown the rocker arm 40, the pivot rod 320, the pivot rod retainer 330, and the valve bridge 310. The pivot rod 320 comprising a pivot rod head 329, a pivot rod neck 327, and a pivot rod body 325 with a pivot rod bottom 425 is more clearly illustrated. Also shown is the pivot rod head 329 with the preferred curved shape in the form of a "mushroom" head.

[0029] Figure 4 shows, in better detail, the valve bridge 310 comprising a pivot rod chamber 315, a pair of fastener bores 314, valve stem chambers 405, a bottom valve bridge section 312 and a middle valve bridge section 316. There is shown the pivot rod chamber 315 hollow cylindrical void or chamber configuration, which will complementarily interact or cooperate with the pivot rod body 325. The complimentary configurations of the pivot rod bottom 425 and the corresponding pivot rod chamber bottom 415 will eliminate the flat surface rubbing contact 15 present in prior designs to substantially reduce friction wear between the pivot rod 320 and the valve bridge 310. Additionally, there is shown the divot or dimple 417 at the pivot chamber bottom 415 which will hold engine oil or some other lubricant to provide lubrication between the

pivot rod 320 and the valve bridge 310. The lubrication between the pivot rod bottom 425 and the pivot chamber bottom 415 will further reduce friction wear between the pivot rod 320 and the valve bridge 310.

[0030] Figure 4 also shows, the pivot rod chamber 315 preferably located in the middle valve bridge section 316. The middle valve bridge section 316 may be either a raised body portion as shown here or flush as illustrated in Figure 1, depending on the particular engine application. The bottom valve bridge section 312 provides the valve bridge 310 added structural support and strength as there is now a pivot rod chamber 315 in the valve bridge 310. The bottom valve bridge section 312 is preferably a raised body portion that extends away and downward from the valve bridge 310. Also, shown are the fastener bores 314 typically bored into the valve bridge 310 adjacent to the pivot rod chamber 315. The fastener bores 314 allow the pivot rod 310 to be secured in the pivot rod chamber 315 via the pivot rod retainer 330 (shown in Figures 6 & 7). Figure 4 also shows the preferred flat shape of the pivot rod retainer 330.

[0031] Figure 5 illustrates a perspective view of a second embodiment of the valve actuation linkage mechanism 500 according to the present invention. The second embodiment of the valve actuation linkage mechanism 500 is identical to the first embodiment of the valve actuation linkage mechanism 500 shown in Figure 1. There is one main exception, there is no use of the pivot rod retainer 330 (shown in Figures 3 & 4). The valve actuation linkage mechanism 500 here is preferably held in proper positioning by the close tolerances between the rocker arm 40, the pivot rod 320 and the valve bridge 310 once the valve actuation linkage mechanism 500 is operationally installed in an engine using this embodiment.

[0032] The valve actuation linkage mechanism 500 will operate in a manner substantially similar to that described for the first embodiment of the valve actuation linkage mechanism

300(Figure 3). Once the pivot rod 320 has been installed in the valve bridge 310, the rocker arm 40 will cooperate with the pivot rod 320/valve bridge 310 combination to actuate corresponding valves (not shown). The pivot rod 320 rotates freely and moves about the pivot rod head 329 and pivot rod bottom 425 (shown in Figure 4) as necessary to account for the rotation and translation required for a 4-valve per cylinder engine requiring a valve bridge 310. There is enough play or space in the pivot rod chamber 315 so that the pivot rod body 325 can move back and forth to translate the motion of the rocker arm 40 to the valve bridge 310 to appropriately actuate the valves (not shown) during engine operation.

[0033] Figure 6 shows a perspective view of a pivot rod 320 and valve bridge 310 of the valve actuation linkage mechanism 300 shown in Figure 3. Figure 6 shows the pivot rod 320 and pivot rod retainer 330 secured to the valve bridge 310 by a pair of fasteners 614 inserted into the valve bridge fastener bores 314. The resilient retaining prongs 337 are shown securing the pivot rod 320 about the pivot rod neck 327 to the valve bridge 310 in the pivot rod chamber 315 (shown in Figure 7). Also, the pivot rod retainer 330 comprises a pivot rod retainer area 335 that is configured to allow the pivot rod 320 movement or play within the pivot rod area 335 during valve actuation. Once the pivot rod 320 has been secured to the valve bridge 310, the rocker arm 40 cooperates with the pivot rod 320/valve bridge 310 combination to actuate corresponding valves (not shown). The pivot rod body 325 will preferably move back and forth in the pivot rod chamber and vertically to translate the motion of the rocker arm 40 to the valve bridge 310 and thereby actuate the valves (not shown) during engine operation.

[0034] Figure 7 shows a side view of a pivot rod 320 and valve bridge 310 of the partial valve actuation linkage mechanism 300 shown in Figure 6. There is shown the pivot rod 320 appropriately positioned in the pivot rod chamber 315 and secured to the valve bridge 310 by the pivot rod retainer 330 by a pair of fasteners 614. The fasteners are preferably inserted into a pair of opposing the valve bridge fastener bores 314 located adjacent to the pivot rod chamber 315. The pivot rod retainer 330 is shown securing the pivot rod 320 about the pivot rod neck 327 to the valve bridge 310. Once the pivot rod 320 has been secured to the valve bridge 310, the rocker arm 40 cooperates with the pivot rod 320/valve bridge 310 combination to actuate corresponding valves (not shown).

[0035] Figure 7 shows a pivot rod chamber movement area 715 that allows the pivot rod to move back and forth inside the pivot rod chamber 315 to compensate for the arc motion of the rocker arm 40 (shown in Figure 3) during engine operation. In this manner the vertical motion of the rocker arm 40 can be translated to the valve bridge 310 during engine operation. There is also shown the complimentary round nature of the pivot rod bottom 425 and the pivot rod chamber bottom 415. The complimentary configurations of the pivot rod bottom 425 and the corresponding pivot rod chamber bottom 415 eliminate the flat surface rubbing contact 15 present in prior designs such as shown in Figure 1. Instead of the flat surface contact area 15 (shown in Figure 1), the complimentary curved surfaces of the pivot rod bottom 425 and the corresponding pivot rod chamber bottom 415 result in a contact line or contact line area 725 between both components. The resultant contact line area 725 is smaller than the flat surface rubbing contact 15 shown in Figure 1 and thus substantially reduces friction wear between the pivot rod 320 and the valve bridge 310. Additionally, the pivot rod chamber 315 has a divot or dimple 417 at the pivot rod chamber bottom 415 which will hold engine oil or some other lubricant to provide lubrication between the pivot rod



Age	Sex	Height	Weight	Arm span	Hand span	Hand length	Hand width	Hand area	Hand volume	Hand mass
10	M	140	30	160	18	10	8	80	100	100
11	M	145	35	165	19	11	9	99	110	110
12	M	150	40	170	20	12	10	120	120	120
13	M	155	45	175	21	13	11	143	140	140
14	M	160	50	180	22	14	12	168	160	160
15	M	165	55	185	23	15	13	195	180	180
16	M	170	60	190	24	16	14	224	200	200
17	M	175	65	195	25	17	15	255	220	220
18	M	180	70	200	26	18	16	288	240	240
19	M	185	75	205	27	19	17	323	260	260
20	M	190	80	210	28	20	18	360	280	280
21	M	195	85	215	29	21	19	399	300	300
22	M	200	90	220	30	22	20	440	320	320
23	M	205	95	225	31	23	21	483	340	340
24	M	210	100	230	32	24	22	528	360	360
25	M	215	105	235	33	25	23	575	380	380
26	M	220	110	240	34	26	24	624	400	400
27	M	225	115	245	35	27	25	675	420	420
28	M	230	120	250	36	28	26	728	440	440
29	M	235	125	255	37	29	27	783	460	460
30	M	240	130	260	38	30	28	840	480	480
31	M	245	135	265	39	31	29	899	500	500
32	M	250	140	270	40	32	30	960	520	520
33	M	255	145	275	41	33	31	1023	540	540
34	M	260	150	280	42	34	32	1088	560	560
35	M	265	155	285	43	35	33	1155	580	580
36	M	270	160	290	44	36	34	1224	600	600
37	M	275	165	295	45	37	35	1295	620	620
38	M	280	170	300	46	38	36	1368	640	640
39	M	285	175	305	47	39	37	1443	660	660
40	M	290	180	310	48	40	38	1520	680	680
41	M	295	185	315	49	41	39	1599	700	700
42	M	300	190	320	50	42	40	1680	720	720
43	M	305	195	325	51	43	41	1763	740	740
44	M	310	200	330	52	44	42	1848	760	760
45	M	315	205	335	53	45	43	1935	780	780
46	M	320	210	340	54	46	44	2024	800	800
47	M	325	215	345	55	47	45	2115	820	820
48	M	330	220	350	56	48	46	2208	840	840
49	M	335	225	355	57	49	47	2303	860	860
50	M	340	23							